# TECHNICAL SPECIFICATION



## Powercap® Infinity® Respirator

Black / CEA646-001-100



#### DESCRIPTION

The PowerCap® Infinity® PAPR – a fully integrated TH3 powered air respirator offering four of the highest levels of protection in one intuitive head-mounted unit. Offering 4-in-1 above the neck protection, PowerCap® Infinity® is the perfect choice for many industries where dust poses a danger to health. The unit represents the very latest in Powered Air Purifying Respiratory technology, combining decades of innovation from JSP in the fields of respiratory, head, eye and face protection.

#### OPTIONS

Black (CEA646-001-100) Blue (CEA646-000-500) White (CEA646-000-100)

#### SAFETY STANDARDS

EN 12941 • EN 397 • EN 166 • ANSI/ISEA Z89.1



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



#### SPECIFICATIONS



50 Joules

Lateral Deformation Yes

Impact Resistance

Maximum Temperature



+50°C ABS Shell



ABS

Textile Harness

Yes



Slip Ratchet Wheel



**Reflective Option** Fitted



**JSPCheck** Yes

Classification TH3



Exhalation Valve Twin Exhalation Valve To Reduce CO2 Build-Up

Maximum Total Inward Leakage (TIL) 0.2% When Fitted To PowerCap® Infinity® Respirator

**UK Assigned Protection Factor** 40

Face Seal Type Hypoallergenic Material

Metal Free No

Filter Material **Pleated Media** 



**RADIATION PROTECTION BREAKDOWN filtering effect** Scale Number 2



Manufacturer's Trademark JSP Dagger



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles. В



**BSI Kitemark** Yes



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.





**Electrical Insulation** 1000V



Molten Metal Yes



+5°C



Recyclable Shell



Depth Adjustment **3D Harness** 



Ventilation No



Integrated Eyewear Optional

Optional 4 point chinstrap (EN397 Compliant) Optional

Usage

P R SL (A Reusable Solid & Liquid Particulate Aerosol Filter)

Minimum Filtration Efficiency 99.8%

Nominal Protection Factor 500

Mask Design A Turbo Hood Powered Air Purifiying Respirator (Loose Fitting)

Latex free Yes

Filter Shelf Life 5 Years

Battery Type Rechargeable Lithium-ion 3.6v, 5.2Ah, 18.72Wh. Expected Life Of 500 Cycles When Charged, Stored and Used In Accordance With User Instructions



LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2



Optical Class (1 - Class 1 - High quality for regular use. 2 -Class 2 - Medium quality for occasional use. 3 - Class 3 -Low quality for exceptional use) 1



Resistance to Molten Metals and Hot Solids (optional) 9



Product Weight 1042g



### **Powerful Twin Turbo Performance**

The patented Twin Turbo Technology controls the airflow through the headtop to maximise user comfort and optimise energy efficiency. Real time diagnostics ensure that the twin impeller motor unit delivers the optimum level of airflow depending on the wearer's demands and regulates the intake and internal pressure delivering a minimum of 160 litres a minute of filtered clean air.



#### No need to FACE FIT test

PowerCap® Infinity® removes the need for fit testing, ensuring that a high volume of clean air is delivered to the breathing zone giving a high level of protection.



#### **Head Protection**

The head protection element of the PowerCap® Infinity® is based on the EVO®5 Olympus® industrial safety helmet. The helmet combines a super strong ABS shell designed for superior all day protection with the comfort benefits of the Evolution® 3D-Adjustment<sup>™</sup> harness system.



#### **Panaromic Impact Visor**

The optical class 1 visor conforms to EN166.B offering impact protection at speeds of up to 270 mph (tested using a 6mm steel ball bearing). The visor has a replaceable peel-off visor protector to prolong its life.



#### Tested to the MAX

Hundreds of hours of human treadmill tests were conducted in a purpose built salt dust challenge chamber to optimise mass, balance and sealing elements. Extensive user trials were conducted, putting the PowerCap® Infinity® to the test in a variety of harsh conditions.



#### **Minimal Maintenance**

PowerCap® Infinity® has been developed as a modular system, making it easy to disassemble and reassemble for ease of cleaning and maintenance. To ensure the optimal performance of PowerCap® Infinity® it is important that maintenance is carried out on a regular basis. No specialist tools required.



#### Aerospace

Airports

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Agricultural

Construction and Infrastructure





#### **TH3 Performance**

PowerCap® Infinity® offers respiratory protection to TH3, with a Nominal Protection Factor of 500 (UK APF 40). TH3 is the highest possible rating in the EN12941:1998 + A2:2008 standard.





Real time diagnostics monitor the system and the wearer twice per second, giving the user accurate, dynamic feedback. Periods of high respiratory demand are monitored and catered for by constantly maintaining a positive pressure inside the respirator. Feedback is given on battery and filter condition via the heads up display and audible notifications.



#### **High Efficiency Filters**

The high capacity HEPA filters coupled with the aerodynamically optimised pre-filter covers ensure that PowerCap® Infinity® delivers 160 litres per minute of clean air to the user with maximum battery efficiency. Filters can be effortlessly replaced using an intuitive quick-change bayonet system.

#### Ear Defenders

The PowerCap® Infinity® has been developed to seamlessly integrate with the optional Sonis® helmet mounted ear defenders. Designed by the JSP R&D team and working with a leading UK acoustic engineering research facility, the Sonis® helmet mounted range peaks at an unbeaten SNR 36dB. The helmet adaptor and the cushion surface area work together to provide optimum cushion pressure and comfort.

#### Perfect Fit to Combat Dust

Dust in the workplace is a significant issue. The latest HSE figures (2017) show that 18,000 new cases of work-related respiratory disease were diagnosed. A significant proportion of these were the result of exposure to silica. While the problem is widely acknowledged and use of respiratory equipment is high, it is often not suitable for the person or the environment it is being used in.

#### Page 3 of 5 / Issued 8 Mar 2021 / Copyright 2018 - 2021. JSP Limited. All Rights Reserved



Facilities Management	Food and Drink Manufacturing
Hospitals, Healthcare & Pharmaceuticals	Law Enforcement
Manufacturing	Maritime
Mining, Aggregates and Quarrying	Oil, Gas and Chemical Companies
Rail and Tunnelling	Renewable, Wind and Solar Energy
Scaffolding and Roofing	Sole Trader
Utilities Contractors	Welding
ACCESSORIES	
EVO® Sweatband	Replacement Peel-off Polycarbonate Visor Cover for PowerCap® Infinity®
Powercap® Infinity® Airflow Indicator Test Unit	Powercap® Infinity® Charge Dock and Power Supply
PowerCap® Infinity® Pre-Filters	Powercap® Infinity® Twin Turbo Drive Unit and Visor Carrier Assembly
Powercap® Infinity® Visor with Black Valves	Replacement Helmet for Powercap® Infinity®
Replacement Powercap® Infinity® Battery Pack	Replacement Powercap® Infinity® Face Seal Skirt
Replacement Powercap® Infinity® Filters	Replacement Powercap® Infinity® Harness Strap
Replacement Powercap® Infinity® Pre-Filters with covers	Sonis® Compact Helmet Mounted Ear Defenders
Sonis®1 Helmet Mounted Ear Defenders	Sonis®3 Helmet Mounted Ear Defenders
Stainless Steel Spark Guard for Powercap® Infinity® Pre Filter (1 Pair)	PPE Cleaning Station & Accessories
COMPATIBLE PRODUCTS	

EVO® Sweatband	Replacement Peel-off Polycarbonate Visor Cover for PowerCap® Infinity®
Powercap® Infinity® Airflow Indicator Test Unit	Powercap® Infinity® Charge Dock and Power Supply
Powercap® Infinity® Respirator	$Powercap^{\texttt{R}}$ Infinity $\ensuremath{\mathbb{R}}$ Twin Turbo Drive Unit and Visor Carrier Assembly
Powercap® Infinity® Visor with Black Valves	Replacement Helmet for Powercap® Infinity®
Replacement Powercap® Infinity® Battery Pack	Replacement Powercap® Infinity® Carry Case
Replacement Powercap® Infinity® Face Seal Skirt	Replacement Powercap® Infinity® Filters
Replacement Powercap® Infinity® Harness Strap	Replacement Powercap® Infinity® Pre-Filters with covers
Sonis® Compact Helmet Mounted Ear Defenders	Sonis®1 Helmet Mounted Ear Defenders
Sonis®3 Helmet Mounted Ear Defenders	Stainless Steel Spark Guard for Powercap® Infinity® Pre Filter (1 Pair)

#### RANGE



VIDEOS

youtu.be/jS1Fr-xVS1I

- youtu.be/IMJIVCKiTdo
- youtu.be/u7dUKX-\_vAc

#### DOWNLOADS

#### Image Pack (ZIP)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

